

PLASTIC PROCESSING MACHINE / BAG MAKING MACHINE
DOUBLE DECKER SEALING & CUTTING MACHINE

At Mahindra Plastics Industries, we deal in the manufacturing of double-decker sealing and cutting machines. We deal in highly durable, advanced, highly performing, and corrosion-resistant double-decker sealing and cutting machines. It is a machine made for all those looking to make plain or even t-shirt-like bags. It is made for accurate and compact design. While talking about its prices, it is one of the most reasonable machines available.

Mahindra Plastics Industries is one of the leading double deckers sealing and cutting machine services providers. It offers smooth production, as it is made with the conveyor belt. Moreover, it has all the durable and cutting machine, which provides an excellent performance. To meet the client's requirements, we developed the double-decker sealing and cutting machine today.



[CATALOGUE](#) [CONTACT US](#)

DOUBLE DECKER SEALING AND CUTTING MACHINE VIDEOS TECHNICAL SPECIFICATION

SPECIFICATIONS	455 MM SERVO BOTTOM	610 MM SERVO BOTTOM	710 MM SERVO BOTTOM	810 MM SERVO BOTTOM	915 MM SERVO BOTTOM	1065 MM SERVO BOTTOM	1220 MM SERVO BOTTOM	1400 MM SERVO BOTTOM
Mahindra Plastic Industries	455 MM Servo Bottom Sealing & Cutting Machine	610 MM Servo Bottom Sealing & Cutting Machine	710 MM Side Sealing & Cutting Machine	810 MM Bottom Sealing & Cutting Machine	915 MM Bottom Sealing & Cutting Machine	1065 MM Servo Bottom Sealing & Cutting Machine	1220 MM Servo Bottom Sealing & Cutting Machine	1400 MM Servo Bottom Sealing & Cutting Machine
MIN. FILM WIDTH (in mm):	63.5	63.5	63.5	63.5	63.5	63.5	63.5	63.5
MAX. FILM WIDTH:	406	559	660	762	864	1016	1168	1346
CUT LENGTH:	1 Meter	1 Meter	1 Meter	1 Meter	1 Meter	1 Meter	1 Meter	1 Meter
LINE SPEED:	40 Meter	40 Meter	40 Meter	40 Meter	40 Meter	40 Meter	40 Meter	40 Meter
TOTAL CONNECTED LOAD:	8 KW	8 KW	8 KW	8 KW	8 KW	8 KW	8 KW	8 KW
Main Motor	2HP	2HP	2HP	2HP	2HP	2HP	2HP	2HP
Servo Motor	2 KW	2 KW	2 KW	2 KW	2 KW	2 KW	2 KW	2 KW
AC Drive Make	Delta/INVT	Delta/INVT	Delta/INVT	Delta/INVT	Delta/INVT	Delta/INVT	Delta/INVT	Delta/INVT
Speed	160 Strokes per min. according to size and guage of your bag	160 Strokes per min. according to size and guage of your bag	160 Strokes per min. according to size and guage of your bag	160 Strokes per min. according to size and guage of your bag	160 Strokes per min. according to size and guage of your bag	160 Strokes per min. according to size and guage of your bag	160 Strokes per min. according to size and guage of your bag	160 Strokes per min. according to size and guage of your bag
Key pad setting/Digital Display	For Setting Speed, Size, Count with Digital Display Panel Board	For Setting Speed, Size, Count with Digital Display Panel Board	For Setting Speed, Size, Count with Digital Display Panel Board	For Setting Speed, Size, Count with Digital Display Panel Board	For Setting Speed, Size, Count with Digital Display Panel Board	For Setting Speed, Size, Count with Digital Display Panel Board	For Setting Speed, Size, Count with Digital Display Panel Board	For Setting Speed, Size, Count with Digital Display Panel Board
Static Eliminator	3 Static Rods	3 Static Rods	3 Static Rods	3 Static Rods	3 Static Rods	3 Static Rods	3 Static Rods	3 Static Rods
Un-Winding Stand for One Roll	Friction brake, 1 HP A.C. Motor with AC Drive with sensor On Backside roll on Un-winding	Friction brake, 1 HP A.C. Motor with AC Drive with sensor On Backside roll on Un-winding	Friction brake, 1 HP A.C. Motor with AC Drive with sensor On Backside roll on Un-winding	Friction brake, 1 HP A.C. Motor with AC Drive with sensor On Backside roll on Un-winding	Friction brake, 1 HP A.C. Motor with AC Drive with sensor On Backside roll on Un-winding	Friction brake, 1 HP A.C. Motor with AC Drive with sensor On Backside roll on Un-winding	Friction brake, 1 HP A.C. Motor with AC Drive with sensor On Backside roll on Un-winding	Friction brake, 1 HP A.C. Motor with AC Drive with sensor On Backside roll on Un-winding
SPACE REQUIRED in meters:	L x W x H = 5 x 2 x 1.5 in meters	L x W x H = 5 x 2 x 1.5 in meters	L x W x H = 5 x 2 x 1.5 in meters	L x W x H = 5 x 2 x 1.5 in meters	L x W x H = 5 x 2 x 1.5 in meters	L x W x H = 5 x 2 x 1.5 in meters	L x W x H = 5 x 2 x 1.5 in meters	L x W x H = 5 x 2 x 1.5 in meters
Weight of Machine	700 Kg approx	800 Kg approx	850 Kg approx	1200 Kg approx	1100 Kg approx	1300 Kg approx	1350 Kg Approx	1450 Kg approx



- FEATURES**
 WHAT ARE THE VARIOUS FEATURES OF A DOUBLE-DECKER SEALING & CUTTING MACHINE?
- ✔ Having a Main AC frequency motor along with an AC frequency drive
 - ✔ Having a completely automatic bag length adjustment
 - ✔ Made with the touch screen HM & Having two sealers
 - ✔ Very much easy to operate or user-friendly
 - ✔ Better and smooth finish
 - ✔ Static Charge elimination
 - ✔ Steel table for stacking bags

APPLICATION GALLERY

Bottom Sealing and Cutting Machine Manufacturers in India, BOPP tape bag making machine manufacturer in India, BOPP PP LD HM Side Seal Bag Making Machine, Bottom Sealing and Cutting Machine. This product is highly appreciated for its accurate indexing and micro processor control with digital display. This product is manufactured using latest machinery and advanced technology, to ensure high standards of quality.

